

COMPONENT	UNIT	SPECIFICATION	ANALYSIS METHOD
Aromatics	wt%	max 50	
Benzene	wt%	max 30	
Toluene	wt%	
Density at 15.6C	gr/cm ³	0.8-0.84	ASTM D4052
FBP	°C	max 225	ASTM D86
IBP	°C	min 33	ASTM D86
R.V.P	Kpa	40-65	ASTM D6378
Paraffines	wt%	max 21	
Isoparaffines	wt%	max 21	
Naphtenes	wt%	max 2	
Olefins	wt%	max 20	
Total Sulfur	mg/kg	350	ASTM D5453

Gum Content	mg/100ml	max 50	
Lead Content	Ppb	max 30	
Water Content		...	ASTM E203
Unknown	wt%	...	
Residue	wt%	...	ASTM D86
5% Recovery	°C	min 45	ASTM D86
10% Recovery	°C	...	ASTM D86
20% Recovery	°C	...	ASTM D86
30% Recovery	°C	...	ASTM D86
40% Recovery	°C	...	ASTM D86
50% Recovery	°C	...	ASTM D86
60% Recovery	°C	...	ASTM D86
70% Recovery	°C	...	ASTM D86

80% Recovery	°C	...	ASTM D86
90% Recovery	°C	min 175	ASTM D86
Recovery	°C	...	ASTM D86
Color Sybolt		-16	